



KARTA PRODUKTOWA

DM-1200 Gantry Milling Machine 1200 × 3000 mm





KARTA PRODUKTOWA



Main image of the DM-1200 model – DM-1200 Manual / DRO gantry milling machine
DM-1200 Manual / DRO

DM-1200 Gantry Milling Machine

Manual gantry milling machine with optional DRO, a 1200 × 3000 mm table and a 7.5 kW milling head

DM-1200 is a DM-1200 gantry milling machine designed for machining large plates, housings, frames, castings and structural components. The machine is suitable for face milling, machining mounting surfaces, drilling and workshop operations requiring a stable gantry construction.

The symmetrical gantry frame provides high rigidity during more demanding cutting conditions, while table support along the entire travel length helps maintain consistent machining accuracy. The **Manual / DRO** version can be equipped with a digital axis position readout, facilitating workpiece setup, dimensional control and repeatable operator work.

1200

Table Width

1200 mm

3000

Table Length

3000 mm / optional 4000 mm



KARTA PRODUKTOWA

1600

Distance Between Columns

1600 mm

7.5

Milling Head Power

7.5 kW / optional 11 kW

DM-1200 – wider DM-1200 variant for stable machining of large faces.

The model offers a 1200 × 3000 mm table with an optional 4000 mm length, 1600 mm clearance between the columns, X/Y/Z-axis travel of 3000 / 1200 / 500 mm, a 7.5 kW milling head with an optional 11 kW version, a 5.5 kW table-drive motor with an optional 7.5 kW version and Manual / DRO configuration options.


Product Gallery

Images and Key Components of the DM-1200 Model

DM-1200 Equipment Components and Operating Systems



KARTA PRODUKTOWA



DRO

KARTA PRODUKTOWA



Vertical Head

KARTA PRODUKTOWA



Horizontal Head

KARTA PRODUKTOWA



ISO Spindle

KARTA PRODUKTOWA



Electrical System
Machine Construction

Rigid Gantry Construction for Machining Large Surfaces

The DM-1200 uses a symmetrical gantry frame that increases the rigidity of the entire construction and



KARTA PRODUKTOWA

improves stability during operation under more demanding cutting conditions. The gantry layout enables convenient machining of long components clamped on the worktable.

The table is supported along the entire travel length, helping maintain consistent cutting accuracy across the full working range. As a result, the machine is suitable for milling faces, datum surfaces, guideways, mounting plates and structural components.

The inverter-controlled X-axis feed drive enables smooth adjustment of table feed speed. A central push-button panel simplifies operation, while the optional DRO system improves the convenience of position setting and dimensional control during operation.

Technical Features

Key Features of the DM-1200

Symmetrical gantry construction provides high rigidity even under more demanding cutting conditions.

Full table support along the entire travel length helps maintain consistent machining accuracy.

Inverter-controlled X-axis drive enables smooth adjustment of table feed speed.

7.5 kW milling head with an optional 11 kW version ensures efficient machining of faces, grooves and mounting surfaces.

Central push-button panel simplifies machine operation and control of basic working functions.

DRO option facilitates axis position control, workpiece setup and repeatable machining.

1200 × 3000 mm table allows machining of larger plates, frames and housings.

Optional 4000 mm table length increases capacity for working with longer components.

Versions and Equipment

Manual / DRO – Configuration for Workshop and Production

Manual version – classic operator-controlled configuration for milling large surfaces.



KARTA PRODUKTOWA

DRO version — digital axis position readout improves operating convenience and reduces the risk of measurement errors.

Vertical head — designed for milling faces, grooves and process surfaces.

Horizontal head — expands the range of side machining and operations requiring a different tool orientation.

Applications

Where is the DM-1200 gantry milling machine suitable?

The DM-1200 is designed for machining large surfaces, welded components, housings, mounting plates, machine frames and castings. Its gantry construction provides stability, while the larger 1200 × 3000 mm table allows work with wider workpieces and components requiring greater clearance between the columns.

Machine production — machining frames, plates, housings and structural components.

Repair facilities — refurbishment of mounting and datum surfaces on large parts.

Toolrooms — milling faces, grooves, datum surfaces and working surfaces.

Steel industry — machining welded structures and heavy technical components.

Single-piece machining — workshop, prototype and repair work.

Plate machining — milling datum surfaces and mounting faces.

DM-1200 Specifications

Technical Specifications of the DM-1200 Model

Model **DM-1200**

Machine Type **DM-1200 Manual / DRO Gantry Milling Machine**

Control / Configuration **Manual operation, optional DRO digital readout**

Table Dimensions **1200 × 3000 mm**

Optional Table Dimensions **1200 × 4000 mm**



KARTA PRODUKTOWA

Distance Between Columns **1600 mm**

X-Axis Travel **3000 mm / optional 4000 mm**

Y-Axis Travel **1200 mm**

Z-Axis Travel **500 mm**

Milling Head Power **7.5 kW / optional 11 kW**

Table Drive Motor Power **5.5 kW / optional 7.5 kW**

Construction **High-rigidity symmetrical gantry frame**

Table Support **Table supported along the entire travel length**

X-Axis Feed Drive **Inverter-controlled motor for variable feed**

Operation **Central push-button panel / operator console**

Selected Components **DRO, vertical head, horizontal head, ISO spindle, electrical system**

Applications **Face milling, machining of plates, frames, housings, castings and mounting surfaces**