



KARTA PRODUKTOWA

DTL-31 Double-Column Vertical Turning Lathe – Manual / DRO 3150 mm





DTL-31 Double-Column Vertical Turning Lathe – Manual / DRO

Double-Column Lathe



KARTA PRODUKTOWA

DTL-31 Double-Column Vertical Turning Lathe

Double-column vertical turning lathe for heavy machining of workpieces with turning diameters up to 3150 mm

DTL-31 is a heavy-duty vertical turning lathe of the **double-column** type, designed for machining large and massive components in industrial, power generation, mining and manufacturing facilities.

The design is based on a rigid, symmetrical arrangement, a robust working table, two working heads and guideways designed for high-load operation. The DTL-31 model offers a turning diameter of up to **3150 mm** and a table diameter of **2250 mm** with an option of **2500 / 2800 mm**.

3150

Max. Turning Diameter

3150 mm

2250

Table Diameter

2250 mm, opcjonalnie 2500 / 2800 mm

12T

Table Load Capacity

12 t, optional 20 / 30 t

55

Main Motor Power

55 kW

Heavy-duty machine for large industrial components.

The DTL-31 combines a robust double-column construction, two working heads, hydrostatic table bearings, 40Cr steel gearboxes and PLC control for safe and repeatable operation.

Photo Gallery

Images and Equipment Components


Technical Machine Images




KARTA PRODUKTOWA



Main Machine View



KARTA PRODUKTOWA




Gearbox




KARTA PRODUKTOWA

Working Table



Symmetrical Construction
Standard Equipment

KARTA PRODUKTOWA



Chuck Jaws

KARTA PRODUKTOWA



Tool Holder

KARTA PRODUKTOWA



Leveling Wedges and Screws

KARTA PRODUKTOWA



Hand Tools

KARTA PRODUKTOWA



Oil Can
Optional Equipment



KARTA PRODUKTOWA



DRO

KARTA PRODUKTOWA



KARTA PRODUKTOWA

Oil Cooler



Chip Conveyor

KARTA PRODUKTOWA





KARTA PRODUKTOWA

Milling Head

KARTA PRODUKTOWA



Grinding Head
Industrial Applications



Heavy Industry

KARTA PRODUKTOWA



Mining



KARTA PRODUKTOWA




Power Generation



KARTA PRODUKTOWA



Structural Fabrication



Machining Large Components
Technical Features



KARTA PRODUKTOWA

Key Features of the DTL-31

High-quality castings and a rigid, symmetrical double-column construction.

40Cr alloy-steel gears and forged shafts in the gearbox.

Two working heads – one for finish turning and the other for rough machining.

Hydrostatic bearings enabling machining of heavy workpieces.

4-jaw chuck with auxiliary T-slots for secure workpiece clamping.

Ram head with a swivel range from -30° to +30° for machining tapered surfaces.

Wear-resistant guideways with a ZnAl10-5 alloy lining for smooth movement.

PLC control ensuring safe and reliable machine operation.

Applications

Where is the DTL-31 lathe suitable?

The DTL-31 is designed for machining large, heavy and oversized components, especially where high system rigidity, a stable working table and safe workpiece clamping are required.

Heavy industry – machining large housings, rings, discs and machine components.

Power generation – turbine elements, flanges, plant components and generator subassemblies.

Mining – large machine parts, housings, wheels, rollers and drive components.

Structural fabrication – welded components, rings, plates and workpieces requiring vertical turning.

DTL-31 Specifications



KARTA PRODUKTOWA

Technical Specifications for the DTL-31 Model

Model **DTL-31**

Machine Type **Vertical Turning Lathe — double-column vertical turning lathe**

Version **Double-column, Manual / DRO**

Maximum Turning Diameter **3150 mm**

Table Diameter / Size **2250 mm, opcjonalnie 2500 / 2800 mm**

Maximum Workpiece Height **1600 mm, opcjonalnie 2000 / 2500 mm**

Table Load Capacity **12 tonnes, optional 20 / 30 tonnes**

Main Motor Power **55 kW**

Number of Working Heads **2 heads — for rough and finish machining**

Head Swivel Range **-30° to +30°**

Workholding Chuck **4-jaw chuck with auxiliary T-slots**

Gearbox **40Cr alloy-steel gears and forged shafts**

Table Bearings **Hydrostatic bearings for high-load operation**

Guideways **Wear-resistant ZnAl10-5 alloy lining**

Control **PLC; Manual / DRO version available**

Standard Equipment **Chuck jaws, tool holder, leveling wedges and screws, hand tools, oil can**

Optional Equipment **DRO, oil cooler, chip conveyor, milling head, grinding head**

Applications **Heavy industry, mining, power generation, structural fabrication, machining large components**