



KARTA PRODUKTOWA

DTL-40M Vertical Turning Lathe 4000 mm





Main image of the DTL-40M model

DTL-40M CNC double-column vertical turning and milling machining centre, 4000 mm

DTL-40M Vertical Turning Lathe

Double-column CNC vertical turning lathe for heavy machining of workpieces up to 4000 mm

DTL-40M is a CNC vertical turning lathe designed for precise and stable machining of large industrial workpieces. The machine enables machining of components with a maximum turning diameter of **4000 mm** and a table load capacity of **32 tonnes**.

The model was designed for heavy industrial duty. A rigid box-type construction with reinforced ribs, precision spindle bearings, a drive with accurate C-axis positioning and an optional automatic tool changer (ATC) enable efficient multi-task machining.



KARTA PRODUKTOWA

4000

Max. Turning Diameter

4000 mm

3000

Table Diameter

3000 mm, optional 3500 mm

2000

Max. Workpiece Height

2000 mm, optional 2500 mm

32T

Table Load Capacity

32 t

DTL-40M – heavy-duty CNC vertical turning lathe for large industrial workpieces.

The model offers a maximum turning diameter of 4000 mm, a 3000 mm table with an optional 3500 mm version, a 32 t table load capacity, a workpiece height of 2000 mm with an optional 2500 mm version, a 55 kW main motor with an optional 75 kW version and equipment for multi-task machining.

Photo Gallery

Images and Key Components of the DTL-40M Model

5 images showing the machine's key components and functions



Automatic ATC Tool Changer



KARTA PRODUKTOWA



Turning on the Lathe



Drilling and Tapping on the Lathe

KARTA PRODUKTOWA



Tool Setter



Workpiece Probe
Technical Features

Key Features of the DTL-40M

Rigid box-type construction with reinforced ribs ensures very high rigidity and stability during heavy machining.

Preloaded double-row roller bearing ensures precise spindle rotation and high turning accuracy.



KARTA PRODUKTOWA

Powered spindle with an ISO taper enables milling, drilling, tapping, grinding and other multi-task operations.

Precision gearbox and drive mechanism are used for accurate C-axis indexing.

Optional automatic ATC tool changer improves multi-tool machining of large workpieces.

High table load capacity enables stable machining of heavy components weighing up to 32 tonnes.

Applications

Where is the DTL-40M lathe suitable?

The DTL-40M is designed for machining large and heavy industrial workpieces, such as rings, flanges, housings, power-generation components, machine parts, bearing components and workpieces requiring turning, drilling, milling or tapping on a single machine.

Heavy industry – machining large housings, castings and machine components.

Power generation industry – turning and machining turbine components, rings and large technical components.

Flange and ring production – stable machining of workpieces with large diameters and high mass.

Large-scale machining facilities – for precision machining of components up to 4000 mm in diameter.

DTL-40M Specifications

Technical Specifications of the DTL-40M Model

Model **DTL-40M**

Machine Type **CNC Vertical Turning Lathe**

Configuration **Double-column vertical turning lathe for turning and multi-task machining**

Max. Turning Diameter **4000 mm**

Table Diameter **3000 mm, optional 3500 mm**

Max. Workpiece Height **2000 mm, optional 2500 mm**

Table Load Capacity **32 t**

Main Motor Power **55 kW, optional 75 kW**



KARTA PRODUKTOWA

Tool Spindle **Powered spindle with ISO taper**

Available Operations **Turning, milling, drilling, tapping, grinding**

Gearbox **Precision gearbox and drive mechanism for C-axis indexing**

ATC **Optional automatic tool changer for multi-tool machining**