



## KARTA PRODUKTOWA

---

### DTL-63F/CNC Vertical Turning Lathe 6300 mm





Main image of the DTL-63F/CNC model  
CNC Vertical Turning Lathe

### DTL-63F/CNC Vertical Turning Lathe

Double-column CNC vertical turning lathe with a fixed crossbeam for machining workpieces up to 6300 mm

**DTL-63F/CNC** is a **double-column CNC vertical turning lathe** with a fixed crossbeam, designed for precise and stable machining of very large industrial workpieces. The machine enables machining of components with a maximum turning diameter of up to **6300 mm** and a table load capacity of **32 tonnes**, optionally up to **50, 70 or 120 tonnes**.

The model was designed for high rigidity and repeatable accuracy. High-quality castings, a symmetrical gantry construction, hydrostatic table bearings and hydrostatic guideways ensure smooth and efficient machining of disc-shaped workpieces, rings, flanges and large technical components.

6300  
Max. Turning Diameter



## KARTA PRODUKTOWA

---

6300 mm

4500

Table Diameter

4500 mm, optional 5000 / 5700 mm

2000

Max. Workpiece Height

2000 mm, optional 2500 / 3000 mm

32T

Table Load Capacity

32 t, optional 50 / 70 / 120 t

**DTL-63F/CNC – double-column CNC vertical turning lathe with a fixed crossbeam.**

The model offers a maximum turning diameter of 6300 mm, a 4500 mm table with an optional 5000 or 5700 mm version, a 32 t table load capacity with an optional 50, 70 or 120 t version, a workpiece height of 2000 mm with an optional 2500 or 3000 mm version, a 75 kW main motor with an optional 90 or 110 kW version and a CNC system with AC drive and speed control via a VDF unit.

Photo Gallery

### **Images and Key Components of the DTL-63F/CNC Model**

Images showing the machine's key components and functions



## KARTA PRODUKTOWA



CNC Control

## KARTA PRODUKTOWA

---



MPG Handwheel




Spindle Rotary Encoder

## KARTA PRODUKTOWA

---



Speed Reducer



Hydrostatic Guideways  
Technical Features

### Key Features of the DTL-63F/CNC

**High-quality LEF / VSR castings** and a rigid, symmetrical double-column construction provide stability during machining.

**2 or 1 ram head** — configurable with one CNC head for finish machining and one manual head for rough



## KARTA PRODUKTOWA

---

turning.

**AC main motor with a VDF unit** provides smooth adjustment of machine operating speeds.

**Hydrostatic table bearings** and high table load capacity enable stable machining of heavy workpieces.

**Fixed crossbeam** provides high rigidity, productivity and accuracy when machining disc-shaped components.

**Hydrostatic guideways** improve motion smoothness, durability and machine operating stability.

Applications

### Where is the DTL-63F/CNC lathe suitable?

The DTL-63F/CNC is suitable for machining very large disc-shaped workpieces, rings, flanges, housings, bearing components and industrial parts that require stable clamping on a large table and precise CNC machining.

**Heavy industry** – machining large housings, castings and structural components.

**Flange and ring production** – stable machining of round and disc-shaped workpieces.

**Bearing industry** – turning large rings, raceways and rotary components.

**CNC machining shops** – for repeatable and accurate machining of workpieces up to 6300 mm in diameter.

DTL-63F/CNC Specifications

### Technical Specifications of the DTL-63F/CNC Model

Model **DTL-63F/CNC**

Machine Type **CNC Vertical Turning Lathe**

Construction **Double-column / gantry construction with a fixed crossbeam**

Configuration **CNC**

Max. Turning Diameter **6300 mm**

Table Diameter **4500 mm, optional 5000 mm or 5700 mm**



## KARTA PRODUKTOWA

---

Max. Workpiece Height **2000 mm, optional 2500 mm or 3000 mm**

Table Load Capacity **32 t, optional 50 t, 70 t or 120 t**

Main Motor Power **75 kW, optional 90 kW or 110 kW**

Control **Siemens 828D / Siemens 840D / Fanuc Oi-mate TD / Fanuc Oi-TD / Fanuc 32i**

Main Drive **AC motor with VDF unit for variable speed control**

Table Bearings **Hydrostatic bearings providing high load capacity**

Guideways **Hydrostatic Guideways**