




KARTA PRODUKTOWA

DTL-63S-CNC Vertical Turning Lathe 6300 mm





Main image of the DTL-63S-CNC model
CNC Vertical Turning Lathe

DTL-63S-CNC Vertical Turning Lathe

CNC vertical turning lathe with a single movable column for machining workpieces up to 6300 mm

DTL-63S-CNC is a CNC vertical turning lathe with a **single movable column**, designed for precise machining of large and heavy industrial workpieces. The machine enables turning of components with a maximum diameter of **6300 mm** and operation with a table load capacity of **32 t**, optionally up to **50 or 70 t**.



KARTA PRODUKTOWA

The design, based on high-quality castings, a large ram-head section and hydrostatic table bearings, provides high stability during machining of oversized components. The movable column facilitates loading and unloading of large and heavy workpieces.

6300

Max. Turning Diameter

6300 mm

4500

Table Diameter

4500 mm, optional 5000 / 5700 mm

3000

Max. Workpiece Height

3000 mm, optional 3500 / 4000 mm

32T

Table Load Capacity

32 t, optional 50 / 70 t

DTL-63S-CNC – CNC vertical turning lathe with a single movable column.

The model offers a maximum turning diameter of 6300 mm, a 4500 mm table with an optional 5000 or 5700 mm version, a workpiece height of 3000 mm with an optional 3500 or 4000 mm version, a table load capacity of 32 t with an optional 50 or 70 t version and a 75 kW main motor.

Photo Gallery

Images and Key Components of the DTL-63S-CNC Model

Images showing the machine's key components and functions



KARTA PRODUKTOWA



CNC Control

KARTA PRODUKTOWA



Central Lubrication System

KARTA PRODUKTOWA



Hydraulic Unit

KARTA PRODUKTOWA



Electrical Cabinet Air Conditioner



KARTA PRODUKTOWA



Packaging

Technical Features

Key Features of the DTL-63S-CNC

High-quality LEF / VSR castings and a rigid, symmetrical construction provide stability during machining of heavy workpieces.



KARTA PRODUKTOWA

Large ram-head section enables efficient machining of heavy and tall industrial components.

AC main motor with a VDF unit provides smooth speed adjustment and stable main-drive operation.

Hydrostatic table bearings provide high load capacity and smooth operation under heavy loads.

Movable column facilitates loading and unloading of large and heavy workpieces.

Auxiliary equipment includes, among others, central lubrication, a hydraulic unit and electrical cabinet air conditioning.

Applications

Where is the DTL-63S-CNC lathe suitable?

The DTL-63S-CNC is suitable for machining large and heavy industrial workpieces, such as rings, flanges, housings, power-generation components, heavy machinery components, turbine parts and components requiring stable clamping and precise CNC machining.

Heavy industry – machining large housings, castings and structural components.

Power generation – turning turbine components, large rings and technical components.

Flange and ring production – stable machining of workpieces with large diameters and high mass.

Large-scale machining facilities – for components with turning diameters up to 6300 mm.

DTL-63S-CNC Specifications

Technical Specifications of the DTL-63S-CNC Model

Model **DTL-63S-CNC**

Machine Type **CNC Vertical Turning Lathe**

Construction **Single Movable Column**

Configuration **Single-column, CNC**

Max. Turning Diameter **6300 mm**

Table Diameter **4500 mm, optional 5000 mm or 5700 mm**



KARTA PRODUKTOWA

Max. Workpiece Height **3000 mm, optional 3500 mm or 4000 mm**

Table Load Capacity **32 t, optional 50 t or 70 t**

Main Motor Power **75 kW**

Control **Siemens 828D s.l. / Siemens 840D s.l. / Fanuc 0i-TD / Fanuc 32i**

Main Drive **AC motor with VDF unit for variable speed control**

Table Bearings **Hydrostatic bearings providing high load capacity**

Selected Equipment Components **CNC, central lubrication system, hydraulic unit, electrical cabinet air conditioner, packaging**